

Water Chiller

**MCK**



# MCK

The water chiller **MCK** consists of a cooling unit in the upper part and a pump plus isolated water tank (made of stainless steel) in the lower section. The unit is conveniently constructed from a frame with removable side panels, allowing easy access to the inner components. The ventilator is assembled at the top part of the unit blowing the warm air upwards.

The new generation of **MCK** units is equipped with high efficiency micro-channel condenser which allows for a very compact framework. The unit models 50 -181 are mobile on wheels. The larger units are standing on four corner-feet in standard. Wheels for large units are provided as option. All **MCK** units are equipped with an electric heating rod. The **MCK** functions fully automatically and requires no supervision.

The cooling and heating units **MCK** are available in twelve different models, the range of performance is between 6,2 and 71,3 kW. Larger units with higher capacity up to 285kW and units with different voltage levels can be built to order.

## APPLICATIONS

- Cooling and heating of must, wine, beer and other liquids such as cider, carbonated soft-drinks, distillates etc.
- Fermentation temperature control
- Tartaric stabilisation of wines and biological reduction of acids
- Cool storage of wine until bottling
- Maturation of young beer
- Cooling and stabilisation of distillates
- Room temperating of halls and storage rooms - only possible with additional fan coils

## WATER TEMPERATURE RANGE

from -10°C to +40°C (from 14°F to 104°F)

## AMBIENT TEMPERATURE RANGE

from +10°C to +32°C (from 50°F to 89,6°F)

## SUITABLE FOR INDUSTRIES



## CHARACTERISTICS

- Hermetically closed motor compressor (Scroll)
- Complete cooling water circuit with highly efficient micro-channel condenser, insulated stainless steel water tank, centrifugal pump and electric heating rod
- Pressure switch integrated in the cooling circuit for pump control - pump protection and energy-saving
- Integrated level-switch and integrated by-pass for pump protection and tank circulation
- All water parts in the unit are isolated
- Stainless steel frame with painted front board
- MCK 50 - 181 mobile on wheels (in standard); wheels for larger units possible as option
- Easy access to the inner components due to easy removable side-boards
- Ventilator on the top part, air-blow direction upwards
- Refrigerant R410A
- Protection type of the chiller is IP54 minimum
- It is required to add Glycol (30 - 35%) to the cooling water by outlet temperatures below +7°C.

			MCK 50	MCK 90	MCK 110	MCK 141	MCK 181	MCK 221	MCK 271	MCK 321	MCK 361	MCK 441***	MCK 541***	MCK 641***
TECHNICAL DATA	Cooling capacity *	kW HP	6,2 8,31	11,5 15,42	13,9 18,64	16,6 22,26	20,0 26,82	25,3 33,93	29,9 40,10	37,0 49,62	45,5 61,02	50,7 67,99	59,9 80,33	71,3 95,61
	Heating capacity	kW	3,0	3,0	3,0	4,5	4,5	4,5	4,5	4,5	4,5	4,5	4,5	4,5
	Electrical supply		400V / 3Ph / 50Hz (other options by inquiry)											
	Max. absorbed power Max. current consumption	kW A	5,2 10,2	7,0 12,9	7,9 15,2	7,9 15,2	9,6 19,9	12,1 20,8	13,7 23,4	17,9 30,4	19,7 34,4	20,0 34,9	26,3 45,1	30,1 50,3
	Noise level **	dB (A)	71	71	71	71	71	71	71	77	77	77	77	77
	Tank volume	l	120	120	120	120	120	300	300	300	300	300	300	300
	Type of pump		Grundfos CM 10-2											
	Dimensions (L x W x H) Weight	mm kg	850 (715) x 715 x 1.575					1.050 x 1.050 x 2.055						
		175	185	190	200	210	300	320	360	380	400	420	430	

\* Cooling capacities at an ambient temperature of +32°C (89,6°F) and a water temperature of +15°C (59°F).  
\*\* At a distance of 1 m  
\*\*\* Standard version with 1 cooling circuit. The models MCK 441, 541, 641 are optionally available with 2 cooling circuits, with bigger water tank (400l) and bigger frame-size (2.000 x 1.000 x 2.055 mm).  
Specifications subject to change.